

User Interfaces Development in openDIEL

Argens Ng (HKU), Tanner Curren (Maryville College)


Mentor: Kwai Wong (UTK)

OpenDIEL – Introduction

- Open Distributive Interoperable Executive Library
- Cooperation between loosely coupled modules
- Uses MPI (Message Passing Interface)
- Outputs single executable
- Crucial in combining multiple simulation scenario !!

OpenDIEL – Manual

- User has to provide:
 - Modules (Executable, C module, Fortran Module, Executable)
 - Configuration File (LibConfig)
 - Driver (C - File)




OpenDIEL – Enhancements

- ModMaker
- Timer
- I/O Improvements
- Fortran Support

ModMaker – Introduction

- Transform at source code level
- No longer compiles into standalone executable
- Compiles into a library



ModMaker – Workflow

```
#include "mpi.h"  
#include "stdio.h"  
#include "test.h"
```

```
int main(int argc, char** argv)
```

```
{
```

```
    int rank;
```

```
    int size;
```

```
    int rc;
```

```
    rc |= MPI_Init (&argc, &argv);
```

```
    MPI_Comm_rank (MPI_COMM_WORLD, &rank);
```

```
    MPI_Comm_size (MPI_COMM_WORLD, &size);
```

```
    printf ("I am process %d out of all %d processes\n", rank, size);
```

```
    MPI_Barrier (MPI_COMM_WORLD);
```

```
    MPI_Finalize();
```

```
    return 0;
```

```
}
```



1

ModMaker – Workflow

2

Identifying Feature



```
int main(int argc, char** argv)
{
    int rank;
    int size;
    int rc;

    rc |= MPI_Init (&argc, &argv);
    MPI_Comm_rank (MPI_COMM_WORLD, &rank);
    MPI_Comm_size (MPI_COMM_WORLD, &size);
    printf ("I am process %d out of all %d processes\n", rank, size);
    MPI_Barrier (MPI_COMM_WORLD);
    MPI_Finalize();

    return 0;
}
```


ModMaker – Workflow

3

```
Transforming file "test.c" into module "first"  
Old files will be put into directory Archive_modMaker  
3 MPI_COMM_WORLD have been replaced.
```

```
We have found something that may need to be changed in your code for the following reason:
```

```
    Only one Main can exist and it belongs in the driver.c
```

```
5)    int main(int argc, char**argv)
```

```
If you agree on this change press [Enter] or key in [y/Y]. If it is incorrect, key in [n/N] █
```

ModMaker – Workflow



ModMaker – User Participation

```
Transforming file "test.c" into module "first"  
Old files will be put into directory Archive_modMaker  
  
Press Enter to Continue or type "exit" to quit:  
We are about to conduct transformation on test.c.  
Press [Enter] to begin or key-in "n/N" to skip this file.
```

```
Transforming file "test.c" into module "first"  
Old files will be put into directory Archive_modMaker  
3 MPI_COMM_WORLD have been replaced.  
Suspected Main remained unchanged  
Suspected MPI_Init remained unchanged  
Suspected MPI_Finalize remained unchanged
```

ModMaker – User Participation

```
Transforming file "test.c" into module "first"  
Old files will be put into directory Archive_modMaker
```

```
13)          MPI_Comm_rank (MPI_COMM_WORLD, &rank);  
                -----
```

```
14)          MPI_Comm_size (MPI_COMM_WORLD, &size);  
                -----
```

```
18)          MPI_Barrier (MPI_COMM_WORLD);  
                -----
```

```
We have found 3 occurrences of MPI_COMM_WORLD.
```

```
Press [Enter] to authorize every change or key-in "n/N" to authorize one-by-one.
```

ModMaker – Pattern Matching

- Two options were considered
 - Matching by character
 - Matching by string
- Matching by string is used
 - Simplicity
 - Similar performance

$$O(n, s) = ns$$

n = string size, s = document size (measured in character)

Text	/	*	T	h	i	s	i	s
Pattern 1	i	n	t		m	a	i	n
Pattern 2	M	P	I	_	I	n	i	t
No match x 2	/	*	T	h	i	s		i
No match x 2		*	T	h	i	s		i

Text	/	*	T	h	i	s	i	s
Pattern 1	i	n	t		m	a	i	n
No match	/	*	T	h	i	s		i
No match		*	T	h	i	s		i
Pattern 2	M	P	I	_	I	n	i	t
No match	/	*	T	h	i	s		i
No match		*	T	h	i	s		i


ModMaker – Syntactic Freedom

```
1) int main(int argc, char** argv) { \n
2) MPI_Init(&argc, &argv);
3) rc=MPI_Init(&argc, &argv);
4) int rc=MPI_Init(&argc, &argv);
5) int main(intargc, char** argv) { \n
```

- Locating
- Spaces
- Variable Declaration

ModMaker – Modularization

- Function Title
- Statement
- Variable



- BaseCheck (line, tokenList, prevSep, nextSep, msgBundle, replacement, returnValue)

Future Work

- Timer
- Multipler I/O
- ModMaker – Fortran Support